



**SHERWIN  
WILLIAMS.**

# SherLast Block Filler

Description	System Recommendation								
SherLast Block Filler is an Acrylic based crack filler which will fill minor hairline crack and provides good base for subsequent coats with good filling and sanding properties.	<b>On old &amp; Porous Substrates:</b>								
	SherLast Primer Sealer	One coat							
	<b>SherLast Block Filler</b>	<b>1-2 coats to fill imperfections</b>							
	Any recommended top coat	2 Coats							
	<b>On new cured concrete, plastered and gypsum substrates:</b>								
	SherLast AR Primer	1 coat							
	<b>SherLast Block Filler</b>	<b>1-2 coats to fill imperfections</b>							
	Any recommended top coat	2 Coats							
Characteristics	<b>Drying Time:</b>								
<b>Colour</b>	White								
<b>Finish</b>	Flat								
<b>Solid contents (% by volume)</b>	62 ± 2 %								
<b>Specific Gravity</b>	1.65- 1.75								
<b>Recommend dry Film Thickness</b>	100 to 200 microns								
<b>Theoretical Coverage:</b>	2 m <sup>2</sup> /kg in one coat								
<b>Flash Point:</b>	Non flammable								
<b>Properties tested as per international Standards</b>	<b>Substrate Temp</b> <b>Dry to Touch</b> <b>Dry to Handle</b> <b>Re-coating Interval</b>								
<b>Viscosity</b>	ASTM D 562								
<b>Specific Gravity</b>	ASTM D 1475								
<b>Gloss</b>	ASTM D 523								
			<table border="1"> <thead> <tr> <th>Minimum</th> <th>Maximum</th> </tr> </thead> <tbody> <tr> <td>2hr</td> <td></td> </tr> <tr> <td>1hr</td> <td></td> </tr> </tbody> </table>	Minimum	Maximum	2hr		1hr	
Minimum	Maximum								
2hr									
1hr									
	23° C	30 mnts	3 h						
	35° C	15 mnts	2 h						
Packing Size	Storage & Handling								
25 kgs. Packing may vary from country to country according to local requirements.	Product must be stored in accordance to national regulations. The product should be kept in well ventilated place protected from heat and direct sunlight. The containers must be kept tightly closed.								



# SherLast Block Filler

Safety Precautions	Application Procedures				
<p>Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapors and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.</p>	<p><b>Surface Preparation:</b> The surface should be properly primed . In case of chalky and difficult surfaces it should be primed with SherLast Primer Sealer.</p> <p><b>Application Conditions:</b> Minimum temperature at 15° C and relative humidity 20 - 85%.</p> <p><b>Application Details:</b></p> <table border="0"> <tr> <td>Application method</td> <td>Scrapper, Putty Knife</td> </tr> <tr> <td>Thinning</td> <td>Paint is ready to use</td> </tr> </table>	Application method	Scrapper, Putty Knife	Thinning	Paint is ready to use
Application method	Scrapper, Putty Knife				
Thinning	Paint is ready to use				
Recommended Uses	Environmental Compliance				
<p>Can be used on most surfaces i.e. plaster, concrete, asbestos, cement sheeting, rendered block work etc. This product is recommended for Exterior and Interior use .</p>	<p><b>VOC Limits Complies to</b></p> <p>LEED EQ credit 4.2</p> <p>MPI E3</p> <p>Green Seal GS 11</p> <p>EPA</p> <p>VOC &lt; 50g/l</p>				